

Wall inlets

Uniflex

Ventilation Slide Uniflex UF



- ✓ For wide houses
- ✓ Independent air control
- ✓ Adjustable spoilers
- ✓ Self-opening
- ✓ Spoilers placed in front of slide
- ✓ Low air resistance due to aerodynamic design

Suitable sectors



Poultry



Pigs



Calves



Other

Options



Manually or centrally operated spoilers



V-shaped jetstream slide



Delay slide



Transparent slide



Telescopic flange



Wind hood



Light trap



Integrated in daylight system

Type	Installation dimensions (mm)			Net surface	Capacity (m3/hr)			Pull force	Stroke length
	W	H	D		10 Pa	20 Pa	30 Pa		
UF-2500	540 mm	345 mm	100 mm	1525 cm ²	1800	2500	2900	2 kg	350 mm
UF-3500	640 mm	395 mm	100 mm	2130 cm ²	2550	3500	4050	2.5 kg	400 mm
UF-5350	840 mm	445 mm	100 mm	3240 cm ²	3900	5350	6150	3.5 kg	450 mm
UF-7500	1040 mm	495 mm	100 mm	4550 cm ²	5450	7500	8650	4.5 kg	500 mm
UF-9000	1120 mm	545 mm	100 mm	5454 cm ²	6550	9000	10350	5 kg	550 mm

Available dimensions

Width	400-1120 mm	In steps of 1 mm
Height	345-670 mm	In steps of 25 mm
Depth	0-500 mm	In steps of 25 mm

