

# KU

Pop-hole Door KU



- ✓ Solid air tight closure
- ✓ Integrated wall frame
- ✓ Insulated slide
- ✓ Self-closing

### Suitable sectors



### Options



Multiple slides



Transparent slide



Telescopic flange



PU filled slide

| Type              | Wall frame dimensions (mm) |        |        | Net opening width | Hole size |        | Stroke length |
|-------------------|----------------------------|--------|--------|-------------------|-----------|--------|---------------|
|                   | W                          | H      | D      |                   | W         | H      |               |
| <b>KU-H1-1000</b> | 1040 mm                    | 540 mm | 100 mm | 1000 mm           | 1050 mm   | 550 mm | 550 mm        |
| <b>KU-H1-1100</b> | 1140 mm                    | 540 mm | 100 mm | 1100 mm           | 1150 mm   | 550 mm | 550 mm        |
| <b>KU-H2-2000</b> | 2086 mm                    | 540 mm | 100 mm | 2001 mm           | 2096 mm   | 550 mm | 550 mm        |
| <b>KU-H2-2200</b> | 2286 mm                    | 540 mm | 100 mm | 2201 mm           | 2296 mm   | 550 mm | 550 mm        |
| <b>KU-H3-3000</b> | 3132 mm                    | 540 mm | 100 mm | 3002 mm           | 3142 mm   | 550 mm | 550 mm        |
| <b>KU-H3-3300</b> | 3432 mm                    | 540 mm | 100 mm | 3302 mm           | 3442 mm   | 550 mm | 550 mm        |

### Available dimensions

|               |             |                   |
|---------------|-------------|-------------------|
| <b>Width</b>  | 200-3432 mm | In steps of 1 mm  |
| <b>Height</b> | 400-640 mm  | In steps of 10 mm |
| <b>Depth</b>  | 0-500 mm    | In steps of 25 mm |

