

AVK

Exhaust Chimney AVK



- ✓ Single or double wall
- ✓ Complete out of HDPE
- ✓ Impact resistant
- ✓ UV-resistant
- ✓ Compact version (80% volume reduction)
- ✓ Different roof profiles available

Suitable sectors



Options



Chimney with rain cap



Chimney with rain ring



Chimney with drip tray



Stiffening ring



Butterfly valve (build-in or build-up)



Damper



Inflow ring



Light trap

Type	Diameter (internal)	Material thickness			
		Welded		Compact	
		Single wall	Double wall	Single wall	Double wall
AVK 370	370 mm	3 mm	14 mm	4 mm	16 mm
AVK 420	420 mm	4 mm	15 mm	4 mm	16 mm
AVK 470	470 mm	4 mm	15 mm	4 mm	16 mm
AVK 520	520 mm	4 mm	15 mm	4 mm	16 mm
AVK 580	580 mm	4 mm	15 mm	4 mm	16 mm
AVK 645	645 mm	4 mm	15 mm	4 mm	16 mm
AVK 730	730 mm	5 mm	16 mm	4 mm	16 mm
AVK 820	820 mm	5 mm	16 mm	4 mm	16 mm
AVK 920	920 mm	5 mm	16 mm	4 mm	16 mm

Available dimensions

Diameter	370-920 mm	ø370/ø420/ø470/ø520/ø580/ø645/ø730/ø820/ø920 mm (internal)
Chimney length	1000-1500 mm	1000/1200/1500 mm

