

GDK



Wall Inlet Curved or Straight Flap Single Turning Point GDK/RDK



- ✓ Curved or straight flap with bottom hinge
- ✓ Optimal air control due to curved flap
- ✓ Self-opening
- ✓ Insulated flap

Suitable sectors



Poultry



Pigs



Calves



Other

Options



Multiple



Unassembled



Deflector
125 mm



Transparent
flap



Telescopic
flange



Wind hood



Light trap



Integrated in
daylight system

Type	Installation dimensions (mm)			Net surface	Capacity (m ³ /hr)			Pull force	Stroke length
	W	H	D		10 Pa	20 Pa	30 Pa		
RDK-2500	540 mm	345 mm	100 mm	1525 cm ²	1800	2500	2900	1.3 kg	440 mm
GDK-2500	540 mm	345 mm	100 mm	1525 cm ²	1800	2500	2900	1.3 kg	520 mm
GDK-3500	640 mm	395 mm	100 mm	2130 cm ²	2550	3500	4050	1.5 kg	580 mm
GDK-5350	840 mm	445 mm	100 mm	3240 cm ²	3900	5350	6150	2 kg	650 mm
GDK-7500	1040 mm	495 mm	100 mm	4550 cm ²	5450	7500	8650	2.2 kg	720 mm
GDK-9000	1120 mm	545 mm	100 mm	5454 cm ²	6550	9000	10350	2.5 kg	790 mm

Available dimensions

Width	200-1120 mm	In steps of 1 mm
Height	345-545 mm	345/370/395/445/495/545 mm
Depth	100-500 mm	In steps of 25 mm

