

Air inlets

WVH-V

Tunnel Inlet WVH-V Multiple Vertical



- ✓ Available in separate sections
- ✓ Curved flap with bottom hinge
- ✓ Optimal air control due to curved flaps
- ✓ Self-opening
- ✓ Insulated flaps

Suitable sectors



Poultry



Pigs



Calves



Other

Options



Separate sections
(reduction
transport volume)



WVH-V2



WVH-V3



WVH-V4



Multiple

Type	Installation dimensions (mm)			Net surface	Capacity (m ³ /hr)			Pull force	Stroke length
	W	H	D		10 Pa	20 Pa	30 Pa		
WVH-V2-12650	1120 mm	790 mm	100 mm	7668 cm ²	9600	12650	14550	6 kg	520 mm
WVH-V3-19000	1120 mm	1185 mm	100 mm	11502 cm ²	14350	19000	21850	9 kg	520 mm
WVH-V4-25300	1120 mm	1580 mm	100 mm	15336 cm ²	19150	25300	29150	12 kg	520 mm
WVH-V2-16150	1420 mm	790 mm	100 mm	9798 cm ²	12250	16150	18600	7 kg	520 mm
WVH-V3-24250	1420 mm	1185 mm	100 mm	14697 cm ²	18350	24250	27900	10 kg	520 mm
WVH-V4-32350	1420 mm	1580 mm	100 mm	19596 cm ²	24500	32350	37250	13 kg	520 mm

Available dimensions

Width	200-3180 mm	In steps of 1 mm
Height	345-2180 mm	Per section: 345/370/395/445/495/545 mm
Depth	100-1000 mm	In steps of 25 mm

