

Air inlets

SK

Counter Rotating Valve SK



- ✓ Stepless adjustable from 0-100%
- ✓ Directly operated by motor or centrally controlled
- ✓ Spring opened or spring closed
- ✓ Insulated flaps
- ✓ With or without flap sealing
- ✓ With or without bird wire

Suitable sectors



Poultry



Pigs



Calves




Other

Options




Vertical



Horizontal



Multiple vertical



Multiple horizontal

| Type | Installation dimensions (mm) | | | Net surface | Capacity (m ³ /hr) | | | Pull force | Stroke length |
|---------------------------|------------------------------|---------|--------|-----------------------|-------------------------------|-------|-------|------------|---------------|
| | W | H | D | | 10 Pa | 20 Pa | 30 Pa | | |
| SK-V10-7700 (V) | 1271 mm | 500 mm | 100 mm | 4657 cm ² | 5600 | 7700 | 8850 | 6 kg | 280 mm |
| SK-V15-11500 (V) | 1883 mm | 500 mm | 100 mm | 6972 cm ² | 8400 | 11500 | 13250 | 7 kg | 280 mm |
| SK-V10-16300 (V) | 1271 mm | 1000 mm | 100 mm | 9889 cm ² | 11900 | 16300 | 18800 | 6 kg | 280 mm |
| SK-V15-24400 (V) | 1883 mm | 1000 mm | 100 mm | 14804 cm ² | 17750 | 24400 | 28100 | 7 kg | 280 mm |
| SK-H2/10-24900 (H) | 1500 mm | 1271 mm | 100 mm | 15091 cm ² | 18110 | 24900 | 28650 | 7 kg | 280 mm |
| SK-H2/15-37500 (H) | 1500 mm | 1883 mm | 100 mm | 22686 cm ² | 28350 | 37500 | 43100 | 7 kg | 280 mm |
| SK-H2/10-33400 (H) | 2000 mm | 1271 mm | 100 mm | 20259 cm ² | 25300 | 33400 | 38500 | 7 kg | 280 mm |
| SK-H2/15-50250 (H) | 2000 mm | 1883 mm | 100 mm | 30455 cm ² | 38050 | 50250 | 57850 | 7 kg | 280 mm |

Available dimensions

Vertical / Horizontal

| | | |
|------------------------|-------------|----------------------|
| Width / Height: | 413-2251 mm | In steps of 122.5 mm |
| Height / Width: | 200-1120 mm | In steps of 1 mm |
| Depth / Depth: | 100-500 mm | In steps of 25 mm |

