



# DR-SK

Blackout Roof Window DR-SK



- ✓ Meets the requirements of KAT/QS/SKAL/MDV/BLK
- ✓ Stepless blackout from 0-100%
- ✓ Uniform light distribution
- ✓ High insulation value
- ✓ Completely assembled
- ✓ Spring closed

### Suitable sectors



Poultry



Pigs



Calves



Other

### Options



PU filled flaps

Type	Installation dimensions (mm)			Net surface	Pull force	Stroke length
	W	H	D			
<b>DR-SK 1026-1030</b>	1026 mm	1030 mm	200 mm	9.600 cm <sup>2</sup>	6 kg	300 mm
<b>DR-SK 1026-1050</b>	1026 mm	1050 mm	200 mm	9.800 cm <sup>2</sup>	6 kg	300 mm
<b>DR-SK 1026-1230</b>	1026 mm	1230 mm	200 mm	11.600 cm <sup>2</sup>	6 kg	300 mm
<b>DR-SK 1026-1250</b>	1026 mm	1250 mm	200 mm	11.800 cm <sup>2</sup>	6 kg	300 mm

### Available dimensions

<b>Width</b>	930-1271 mm	930/1026/1148/1271 mm
<b>Height</b>	800-1300 mm	In steps of 10 mm
<b>Depth</b>	200-500 mm	In steps of 25 mm

